

--

4.7.1.	API/CF,CF-2,CF-4,CI-4/SJ Detergent Oil, Heavy Duty Special II 15 W-40 for gas and / or diesel engines. Tank capacity = 250 gallons bulk	
4.7.2.	Universal Premium Transdraulic Detergent Oil with service rating, J20 C/D, J14C, JDT303, C3/C4, B6, Case/IH MS1207, Ms1210, JIC 145, TCH, TFD,. Tank Capacity = 250 gallons bulk. County requests dye to be added to the oil.	
4.7.3.	Anti-freeze fluid in 1 gal, containers	
4.7.4.	Extended life coolant, Heavy Duty cat EC-1 spec. 50/50 mix in 55 gallon drum	
4.7.5.	SAE 80-90W synthetic gear lube in 55 gallon drum	
4.7.6.	High Temperature Lithium Complex NLGI no. 2GC0Li,120 lb. per barrel	
4.7.8.	Transmission Fluid, Dexronn III	
4.7.9.	Transmission Fluid, Mercon V: Synthetic	
4.7.10.	DexCool or equal; meets ASTM D-3306 and D=434-, gallon containers	
4.7.11.	Extended life coolant. Heavy duty Cat EC-1 spec. 50/50 mix in gallons	
4.7.12.	SAE 5W-20 motor oil API SL ILSAC GF-3. Ford specifications	
4.7.13.	SAE 5W-30 motor oil with API service rating of SJ SH	
4.7.14.	Power Steering Fluid in 1 QR containers for Ford, Gernal Motors and Chrysler Power Steering Units	
4.7.15.	SAE 10W30/ motor oil with API sercive rating SJ SHE	

4.7.16.	Transmission Fluid, Castrol TranSynd Synthetic, 55 Gallon Drim, for use in Allison Automatic Transmission, Oil must be Allison Certified. Transynd, Autran Syn 295, Emgard 2805, or Fleetrite Synthetic ATF ONLY.	
4.7.17.	Total	
4.8.	Maximum Percent Increase for First Renewal	
	Maximum Percent Increase for Second Renewal	
4.8.1.	Minimum Discount from List	
4.10.	Coop?	
4.12.	Cash Discount/Delivery	

No Bid
HeathWood Oil CO, Inc

