



BOONE COUNTY, MISSOURI
Request for Bid #: 04-24JAN13 – Tandem Axle Dump Trucks


ADDENDUM #2 - Issued January 17, 2013

This addendum is issued in accordance with the Bid Response Page in the Request for Bid and is hereby incorporated into and made a part of the Request for Bid Documents. Bidders are reminded that receipt of this addendum **Should be acknowledged** and submitted with Bidder's *Response Form*.

Specifications for the above noted Request for Bid and the work covered thereby are herein modified as follows, and except as set forth herein, otherwise remain unchanged and in full force and effect:

- 1. Change wording on Item 2.3.5. as follows (shaded section indicates change):**
"Front Axle: (Meritor MFS-18-133A **or equal**) SFA (Set Forward Axle), I-Beam type, 18,000 lb. minimum capacity, Wide track."
- 2. Change wording on Item 2.3.28. as follows (shaded section indicates change):**
"Cab, Cowl, Body: Paint schematic: single color RED, design 100 AG; paint type, base coat/clear coat, 1-2 tone. Cab conventional steel or aluminum, wide-body. Cab interior trim, premium; includes thermometer and **optional** compass. Arm rest on each door. Black rubber floor covering. Grab handle: one(1) towel bar type. Anti-slip rubber for cab entry mounted left. Glass: all windows, tinted. Mirrors: two (2) heated, power adjust, rectangular, brackets breakaway type with integral convex mirror heads on both and thermostatically controlled, bright finish heads and brackets. Gauge cluster: English with electronic engine oil pressure, fuel, water temperature, speedometer and tachometer for air brake chassis and voltmeter gauge. Must include odometer display to read miles, trip miles, engine hours and trip hours to be used in conjunction with on-board automated snow and ice control system. Must include a visual and audible warning/alert system for low fuel, low oil pressure, high engine coolant temperature and low battery voltage. Seat for driver and passenger should be air suspension (National Series 2000), high-back with integral headrest, cloth, isolated with two (2) position front cushion adjustment, -3 to 19 degree seat back adjustment and air lumbar support, includes 3-point seat belt, lap and shoulder belt type. Padded dash. Air conditioner with integral heater and defroster. Cab interior and trim: deluxe application with overhead console. Cab rear suspension, air bag type. Fenders shall have flare extensions. Omit front bumper."
- 3. Regarding the location of the Battery System (2.3.17.) and the Fuel Tank (2.3.27.),** it is preferred that they are located on the Driver's side of the truck, under the cab in such a way to ensure that the Tool Box is installed as specified in Section 2.4.10.

By:



Amy Robbins
Senior Buyer

OFFEROR has examined copy of Addendum #2 to Request for Bid **04-24JAN13 – Tandem Axle Dump Trucks**, receipt of which is hereby acknowledged:

Company Name: _____

Address: _____

Phone Number: _____ Fax Number: _____

Authorized Representative Signature: _____ Date: _____

Authorized Representative Printed Name: _____